# Polysafe Standard

## HEAVY-DUTY SAFETY FLOORING WITH A TRADITIONAL DECORATION



# 12

#### **KEY FEATURES**

- BRE Global A+ Rated Product (Certificate No: ENP 336) in major areas such as education and healthcare.
- Incorporates quartz, aluminium oxide, silicon carbide particles and natural recycled aggregates, to improve traction and safety underfoot.
- Proven to be an easier to clean standard safety flooring.
- Best selling range offering extremely good value.
- Fully HSE compliant, with slip resistance assured for the guaranteed life of the product - ≥36 result achieved on RRL Pendulum wet test - 4S Rubber (Slider 96), with a surface roughness of Rz ≥20µm.
- Suitable for areas subject to water and other contaminant spillages in hygiene critical locations.
- 100% recyclable and contains recycled material.

#### **TYPICAL APPLICATIONS**

Washrooms, Toilet areas, Kitchens, Bar Serving areas, Laundry and Sluice rooms, Changing rooms, Cloakrooms.

### **SPECIFICATIONS**

USE AREA CLASS



GAUGE: 2.0mm, 2.5mm, 3.5mm\* AVAILABILITY: Sheet


#### LOCATION: Chelsea Football Club, London

The multitude of colourways available in the Polysafe Standard palette enabled striking reproductions to be made of Chelsea's evolution of club emblems at the Centenary Hall exhibition. The walkway creates an aesthetic focal point to the exhibition's many visitors whilst offering the key requisites of underfoot safety and slip resistance.

"We are very pleased with the flooring CWC recommended and installed. Not only is it safer underfoot for the many people visiting the Centenary Hall but also the colour choice available was ideal for reproducing the inset club logos. The overall effect is excellent"

Simon Arthur Group Operations Director, Chelsea Football Club


# 4 colours are available in 3.5mm gauge for extra heavy-duty areas.




Elmwood 4520



Autumn Beige 4140








Silver Birch 4020\*



Alpine Green 4110





Antique Copper 4120

Redwood 4040\*



Cool Aqua 4570

Cedar Blue 4060\*

Arctic Blue 4130

Twilight 4490



Storm Blue 4560



Lilac Blue 4580



Nordic Grey 4090



Black Walnut 4150



°For details of BRE Environmental Ratings for these ranges installed in specific sector areas, see pages 16-17