

SAARFLOOR NOPPE STUD TILE

- Heavy contract, synthetic rubber floor tiles
- Resilience and comfort underfoot
- Low profile studded surface

SPECIFICATION



3.0mm
4.0mm



20 @ 500 x 500mm = 5m²
16 @ 500 x 500mm = 4m²




4200g/m²
5600g/m²



GENERAL PERFORMANCE EN 12199

3mm
4mm



REACTION TO FIRE EN 13501-1 Class Cfl-S1



CIGARETTE RESISTANCE EN 1399 Method A Rating >4 Method B Rating >3



SLIP RESISTANCE EN 13893 Class DS



ACOUSTICAL IMPACT SOUND REDUCTION EN ISO 10140-3 Rubber floors make a beneficial contribution to impact sound reduction.



VOC EMISSIONS AgBB Very low emissions



ENVIRONMENTALLY PREFERABLE FLOORING SaarFloor-Systems Noppe Stud Tile achieves BRE Global Environmental Generic A+/A rating. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment.



APPLICATIONS SaarFloor-Systems Noppe Stud Tile is suitable for very heavy commercial use in areas of high public circulation such as shopping malls, train stations, airports, department stores, hospitals, educational establishments and other public buildings. Prolonged exposure to oil, grease and fats causes deterioration. SaarFloor-Systems Noppe Stud Tile is suitable for areas where spillage is infrequent, but not garage workshops or food preparation areas. SaarFloor-Systems Noppe Stud Tile is not recommended for exterior use or swimming pool surrounds.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

At the date of issue the data presented is correct.




NOPPE STUD TILE

PERFORMANCE AND PROPERTIES



Refer to BRE Global ratings on www.thegreenguide.org.uk



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Hulstead
FLOORING



May 2014

