

Polysafe™ Verona PUR

Polysafe Verona PUR is ideal for use in areas where contaminant spillages can occur, making slip resistance an important consideration. Typical areas include circulation areas and corridors, dining areas and cafes, classrooms, hospital wards, clinics, laundry and sluice rooms, nursing homes, washrooms, WCs, bar serveries, food preparation areas, canteens and institutional applications. For continually wet areas please refer to our Polysafe Hydro, Hydro Evolve or Quattro ranges.



	Gauge	EN 428/ISO 24346	2.0mm
	Roll Size	EN 426/ISO 24341	2m x 20m = 40m ²
	Total Weight	EN 430/ISO 23997	2600g/m ²
	General Performance	EN 13845 ASTM F1303	Conforms Conforms
	Use Area	EN 685/ISO 10874	
	Resistance to Chemicals	EN 423/ISO 26987	Good chemical resistance
	Reaction to Fire	EN 13501-1 ASTM E648 Aus NCC Spec C1.10-3	Class Bfl-S1 Class 1 Complies
	Abrasion Resistance	EN 13845 EN 649	50,000 cycles Group T
	Enhanced Slip Resistance	EN 13845 AS 4586 Appendix A AS 4586 Appendix D DIN 51130 RRL Pendulum Test Surface Roughness	ESf P4 R11 R11 ≥45 (wet test - 4S Rubber/Slider 96) Rz ≥20µm
<p>The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to HSE Guidelines. For further clarification regarding slip resistance, consult Polyflor.</p>			
	Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	VOC Emissions	AgBB VOC test GBCA/NZGBC Green Star IEQ-VOC Floorscore Finnish M1 Classification	Pass Compliant Certified Certified
	Responsible Sourcing	BES 6001	Excellent
<p>Agrément Assurance - Polysafe Verona PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.</p>			
<p>Environmentally Preferable Flooring - Polysafe Verona PUR achieves BRE Global A+ rating (ENP 472) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Silver Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability</p>			
<p>Polysafe PUR - Polysafe Verona PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Verona PUR should not have a polish applied.</p>			
	Hygiene	<p>All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.</p>	
	Safety	<p>Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.</p> <p>As with all Polysafe products, Polysafe Verona PUR should not have a polish applied. The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com. Decoration and shade may vary slightly from the samples shown.</p>	



Polyflor UK Sales Direct: +44 (0)161 767 1122 • Export Sales Direct: +44 (0)161 767 1913
 Sample Requests: +44 (0)161 767 2551 • email: info@polyflor.com • www.polyflor.com



Polyflor Australia Tel: 1800 777 425 • email: sales@polyflor.com.au • www.polyflor.com.au
Polyflor New Zealand Tel: 0800 765 935 • email: sales@polyflor.co.nz • www.polyflor.co.nz

